



**Your Consistent Source for
Pressure-Sensitive Materials**

CORPORATE HEADQUARTERS & SALES

27001 Agoura Road, Suite 100
Calabasas Hills, CA 91301
Toll-Free: (800) 333-3136
Tel: (818) 880-8060
Fax: (818) 880-1144

CHICAGO

870 Greenleaf Avenue
Elk Grove Village, IL 60007
Toll-Free: (800) 766-4939
Tel: (847) 806-1340
Fax: (847) 806-0296

ATLANTA

2865 N. Berkeley Lake Road, Suite 4
Duluth, GA 30096
Toll-Free: (800) 922-5880
Tel: (770) 232-1878
Fax: (770) 232-7133

MANUFACTURING - LAS VEGAS

4855-D W. Harmon Avenue
Las Vegas, NV 89103

ADDITIONAL OFFICES

Phoenix, AZ • Philadelphia, PA

**Catalina Graphic Films Liability Limits
(MUST READ)**

There are so many different types of inks, wall paints and other variables affecting the application success of this product, it is imperative that the end user determine the suitability of this product for the application. Catalina Graphic Films **will not** be held liable for any cost resulting from a failed application of this Wall Graphic product. Printer/End User assumes all risk and cost associated with the application of this product. In the event of a failure and Catalina, at its sole discretion determines the material had manufacturing defects contributing to the failure, will replace the material **only**.

Wall Graphics® Installation Instructions

In General

Wall Graphics are printed vinyl and some care and patience must be exercised during installation to insure satisfactory performance. **Please STOP installation now if your surface has been painted in last 30 days or if textured!**

The following surfaces are OK to apply Catalina Wall Graphics material:

- Smooth, non textured painted matte drywall
- Smooth, non-textured gloss painted drywall
- Other smooth, non-textured, non-porous surfaces such as glass or metal
- Smooth, non-textured wall paper
- Flat, smooth, finished wood surfaces such as doors and paneling

These surfaces are **NOT** recommended:

- Textured wallpaper
- Textured walls (speckled, orange peel, etc)
- Brick or concrete block
- Unpainted drywall
- Outdoor Walls
- Direct applied to vehicles
- Any other surface that is rough, textured, uneven or porous

Specific Application Instructions

- A: Clean the surface thoroughly and allow plenty of dry time. Do not use chemical cleaners!
- B: If your supplier sent the material rolled up, please lay the sheets out and allow 1 day for them to flatten out.
- C: Start at the top edge and work towards the bottom.
- D: If repositioning is necessary, please remove gently to reapply.
- E: After it is in proper position, squeegee out bubbles by working from center of graphic outward.
- F: Wipe entire graphic with soft, dry cloth to remove and dust or residue from application process.